

Nadellager NBXI4535Z-IKO - NBXI4535Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nbxi4535z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
45	---	---	---	NBXI 4535Z		396	45	62	70

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 455025
D ₂	L	B	H			Radial	Radial		
71.5	35	25	14	10	42 200	83 400	148 000	5 000	

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks:
Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952391038
Innendurchmesser	45 mm
Außendurchmesser	62 mm
Dicke	35 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE