

# Nadellager NAXI5040-IKO - NAXI5040-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/naxi5040-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number											
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		d	D	D <sub>i</sub>
	50	NAXI 5040	582	—	—	—	—	—			
Boundary dimensions mm											
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sup>(1)</sup>	r <sup>(2)</sup>	r <sup>(3)</sup>	d <sub>4</sub>	d <sub>5</sub>	d	Assembled inner ring
86.5	40	25.5	17	12	1	1	60	60	75	59	LRT 506025
Load ratings											
Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup>							
Radial		Axial		Radial		Axial					
N		N		N		N					
47 500		41 400		103 000		89 700		4 000			

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remark 1: The outer ring has an oil groove and an oil hole.  
2: Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952391045
Innendurchmesser	50 mm
Außendurchmesser	72 mm
Dicke	40 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE