


## Gelenklager GE SB110A-IKO - SB110A-IKO

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/sb110a-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree $\alpha$
			$d$	$D$	$B$	$C$	$d_k$	$r_1$ (1)	
110	<b>SB 110A</b>	8,95	110	170	93	80	160	1	5
Mounting dimensions mm		Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N	$d_s$		$D_s$			
Min.	Max.(2)			Min.	Max.	Min.	Max.		
115.5	130	164.5	149	1 260 000	7 530 000				

Notes (1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952391540
Innendurchmesser	110 mm
Außendurchmesser	170 mm
Dicke	93 mm
Typ	GE
Schmierung	ohne
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE