


Gelenklager GE GE240ES-2RS-IKO - GE240ES-2RS-IKO

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/ge240es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
240		GE 240ES-2RS	40,4	240	340	140	100	300	1,1	1,1	8	6
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s	D_s	N		N								
Min.	Max.(2)	Max.	Min.	N		N						
247	265	333	296	2 940 000		17 700 000						

Notes(1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952392103
Innendurchmesser	240 mm
Außendurchmesser	340 mm
Dicke	140 mm
Typ	GE
Schmierung	ohne
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE