

## Gelenklager GE GE260ES-IKO - GE260ES-IKO

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/ge260es-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
<b>260</b>	<b>GE 260ES</b>		52,0	260	370	150	110	325	1,1	1,1	7	6
Mounting dimensions mm		Dynamic load capacity $C_d$		Static load capacity $C_s$								
$d_s$		$D_s$		N								
Min.	Max.(2)	Max.	Min.									
267	288	363	320	3 510 000		21 000 000						

Notes(1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952392127
Innendurchmesser	260 mm
Außendurchmesser	370 mm
Dicke	150 mm
Typ	GE
Schmierung	ohne
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE