


Gelenklager GE GE300ES-IKO - GE300ES-IKO

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/ge300es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
300	GE 300ES		76.0	300	430	165	120	375	1.1	1.1	7	6
Mounting dimensions mm			Dynamic load capacity C_d N	Static load capacity C_s N								
d_s		D_s										
Min.	Max.(2)	Min.										
307	336.5	423	371	4 410 000	26 500 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952392165
Innendurchmesser	300 mm
Außendurchmesser	430 mm
Dicke	165 mm
Typ	GE
Schmierung	ohne
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE