


Gelenklager GE GE110GS-IKO - GE110GS-IKO

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/ge110gs-iko>

IKO

SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d_s	D	B	C	d_s	r_1 (1)	r_2 (2)	α	α_1
110	GE 110GS		9,70	110	180	100	70	160	1	1	12	11
Mounting dimensions mm		Dynamic load capacity C_d N		Static load capacity C_s N								
Min.	Max.(?)	Max.	Min.									
115.5	124.5	174.5	154	1 100 000		6 590 000						

Notes(1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952392516
Innendurchmesser	110 mm
Außendurchmesser	180 mm
Dicke	100 mm
Typ	GE
Schmierung	ohne
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE