

Gelenklager GE SBB68-IKO - SBB68-IKO

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/sbb68-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) kg | Boundary dimensions mm(inch) | | | |
|--|---------------------------|----------------|--|---|---------------------------------------|--------------|--------------|
| | Without seal | With seals | | d | D | B | C |
| 107.950 (4 1/4) | SBB 68 | | 8.46 | 107.950 4 ¹ / ₂ | 168.275 6 ⁷ / ₈ | 94.46(3.719) | 80.95(3.187) |
| Radial internal clearance mm Min./Max. | Mounting dimensions mm | | Dynamic load capacity C _d N | Static load capacity C _s N | | | |
| | d _k | d ₁ | | r ₁ max. Min. | r ₂ max. Min. | 1 | 7 380 000 |
| 155(6.102) | 0.13 / 0.23 | 122.6 | 0.8 | 1.1 | 1 | | |

Notes:
(1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952393025 |
| Innendurchmesser | 107.95 mm |
| Außendurchmesser | 168.275 mm |
| Dicke | 94.46 mm |
| Typ | GE |
| Schmierung | ohne |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE