

## Kurvenrollen CR28-B-IKO - CR28-B-IKO

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/kurvenrollen/cr28-b-iko>

IKO

**CAM FOLLOWERS**

Inch Series Cam Followers **With Cage/With Hexagon Hole**



CR28-B

| Identification number         |                         |                             |                         | Mass (Ref.)                 |                   |                    |                    |                                             |                                           |                                        |
|-------------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------|--------------------|--------------------|---------------------------------------------|-------------------------------------------|----------------------------------------|
| Stud dia.<br>mm<br>(inch)     | Shield type             |                             | Sealed type             |                             | g                 | D                  | C                  | d <sub>1</sub>                              | G<br>UNF                                  | G <sub>1</sub>                         |
|                               | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring |                   |                    |                    |                                             |                                           |                                        |
| 19.050<br>(3/4)               |                         | CR 28 B                     |                         |                             | 365               | 44.450 $\pm$ 0.012 | 25.400 $\pm$ 0.012 | 19.050 $\pm$ 0.012                          | F <sub>1</sub> -18                        | 22.225 $\pm$ 0.012                     |
| Boundary dimensions mm (inch) |                         |                             |                         |                             |                   |                    |                    |                                             |                                           |                                        |
| B                             | B <sub>2</sub>          | B <sub>3</sub>              | C <sub>1</sub>          | G <sub>1</sub>              | G <sub>2</sub>    | H                  | r                  | Bearing dimension<br>f<br>Min.<br>mm (inch) | Maximum<br>spinning<br>torque<br>C<br>N·m | Basic dynamic<br>load rating<br>C<br>N |
| 25.8126                       | 44.450 $\pm$ 0.012      | 11.112 $\pm$ 0.012          | 0.794 $\pm$ 0.012       | 4.762 $\pm$ 0.012           | 3.969 $\pm$ 0.012 | 7.938 $\pm$ 0.012  | 1.988 $\pm$ 0.012  | 32.543 $\pm$ 0.012                          | 100                                       | 25 100                                 |
|                               |                         |                             |                         |                             |                   |                    |                    |                                             |                                           | 36 200                                 |

### PRODUKTMERKMALE

|                  |               |
|------------------|---------------|
| Marke            | IKO           |
| N° Ean13         | 3616060462657 |
| Innendurchmesser | 19.05 mm      |
| Außendurchmesser | 44.45 mm      |
| Dicke            | 25.4 mm       |
| Gewicht          | 365 g         |
| Verpackung       | 1             |

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)  
0800 001 076 6  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE