

Winkelgelenke SA SAL8-T-K-DURBAL - DSAL8-T-K-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/dsal8-t-k-durbal>

SAL8-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

| order number | | measurement [mm] | | | | | |
|-------------------|--------------------|------------------|-----|----|----------------|---------------------------------|-------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ | |
| SAL 8 T/K | | 8 | M 8 | 12 | 9,00 | 24 | |
| type | l ₁ min | measurement [mm] | | h | alpha [°] | Tragzahlen C ₁₀ [kN] | weight [kg] |
| SA / SAL 8 T/K | 25 | l ₂ | | 42 | 14 | 12,9 | 0,038 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3663952490007 |
| Innendurchmesser | 8 mm |
| Außendurchmesser | 24 mm |
| Dicke | 12 mm |
| Typ | - |
| Gewicht | 38 g |
| Gewinde | - |
| Schmierung | - |
| Verpackung | - |
| Standard | - |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE