

Gelenklager GE

GAR40-UK-2RS-DURBAL - GAR40-UK-2RS-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/gar40-uk-2rs-durbal>

GAR40-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



| order number | measurement (mm) | | | | | |
|-------------------|------------------|----|----------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| GAR 40 UK-2RS | | 40 | M 39 x 3 | 28 | 23,0 | 92 |

| type | measurement [mm] | | | load rating C ₀ [kN] | weight [kg] |
|---------------------|--------------------|--------------------|-----|---------------------------------------|----------------|
| | l ₁ min | l ₂ min | h | | |
| GAR / GAL 40 UK-2RS | 86 | 48 | 150 | 7 | 180,0 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3616060467652 |
| Innendurchmesser | 40 mm |
| Außendurchmesser | 92 mm |
| Dicke | 28 mm |
| Typ | GE |
| Gewicht | 1800 g |
| Gewinde | Rechtsgewinde |
| Schmierung | ohne |
| Verpackung | 1 |
| Standard | Ohne Standard |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE