

Winkelgelenke SA DSAZPL19-S-DURBAL - DSAZPL19-S-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/dsazpl19-s-durbal>

DSAZPL19-S



male thread:
lubrication required, similar to DIN ISO 12240-4; series K, measurement in inches

Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

| order number | | measurement [mm] | |
|-------------------|------------------|------------------|----------|
| right hand thread | left hand thread | d | G |
| DSAZPL 19 S | | 19,05 | 3/4 - 16 |
| | | | B |
| | | | 22,23 |
| | | | C1 |
| | | | 17,45 |
| | | | d2 |
| | | | 44,45 |

| type | inches | measurement [mm] | | load rating | weight |
|---------------------|---------|------------------|-------|-------------|--------|
| | | l min | h | C0 [kN] | lkg |
| DSAZP / DSAZPL 19 S | 3 / 4 " | 44,45 | 73,03 | 10 | 29,0 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3663952496252 |
| Innendurchmesser | 19.05 mm |
| Außendurchmesser | 44.45 mm |
| Dicke | 22.23 mm |
| Typ | SA |
| Gewicht | 290 g |
| Gewinde | Linksgewinde |
| Schmierung | ohne |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE