

# Winkelgelenke SA

## SAL15-ES-2RS-DURBAL - SAL15-ES-2RS-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/sal15-es-2rs-durbal>

### SAL15-ES-2RS



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


Ball end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
	SAL 15 ES (-2RS)	15	M 14	12	10,0	40	
type	l <sub>1</sub> min	l <sub>2</sub>	h	n [°]	load rating C <sub>0</sub> [kN]	weight [kg]	
SA / SAL 15 ES (-2RS)	34	20	63	8	36,0	0,140	

## PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952498065
Innendurchmesser	15 mm
Außendurchmesser	40 mm
Dicke	12 mm
Typ	SA
Gewicht	140 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	-
Standard	Ohne Standard

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE