

Winkelgelenke SA SAL50-ES-DURBAL - SAL50-ES-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/sal50-es-durbal>

SAL50-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Bad end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 50 ES	50	M 45 x 3	35	30,0	112

type	l ₁ min	l ₂	h	n [°]	load rating C ₀ [kN]	weight [kg]
SA / SAL 50 ES	107	56	185	6	290,0	3,400

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952498706
Innendurchmesser	50 mm
Innendurchmesser	1.969" inch
Außendurchmesser	112 mm
Außendurchmesser	4.409" inch
Dicke	35 mm
Dicke	1.378" inch
Typ	SA
Gewicht	3400 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE