

Winkelgelenke SA

BRTM20-00-501-DURBAL - BRTM20-00-501-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brtm20-00-501-durbal>


BRTM20-00-501



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series R



**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]									
type	type hand thread	left hand thread	d1	d2	d3	d4	d5	d6	d7	d8	d9
BRTM 20 -00	-501		20	M 20 x 1,5	24,5	50	25	18			

measurements [mm]		weight	rotational speed limit	basic load rating				
type	h	l	l3	α [°]	[kg]	nmax [min-1]	dyn. C [N]	stat. C0 [N]
BRTM 20	78	47	28	7,0	0,340	825	17000	11700

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952506760
Innendurchmesser	20 mm
Außendurchmesser	50 mm
Dicke	25 mm
Typ	-
Gewicht	340 g
Gewinde	-
Schmierung	-
Verpackung	-

kontakt@123kugellager.de
0800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE