

Winkelgelenke SA

BRTM20-00-502-DURBAL - BRTM20-00-502-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brtm20-00-502-durbal>

BRTM20-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]									
type	type	type	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂	b ₃	
BRTM 20 -00	-502		20	M 20 x 1,5	24,5	50	25	18			
measurements [mm]		weight	rotational speed limit	basic load rating							
type	h	l	l ₃	α	[°]	[kg]	n _{max}	d _{ym}	stat.	C ₁₀	C ₉₀
BRTM 20	78	47	28	7,0		0,340	825	17000	11700		

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952506777
Innendurchmesser	20 mm
Außendurchmesser	50 mm
Dicke	25 mm
Typ	SA
Gewicht	340 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE