

Gelenkköpfe SI

BRTF30-01-502-DURBAL - BRTF30-01-502-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/si/brtf30-01-502-durbal>

BRTF30-01-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	h ₁	h ₂
BRTF 30 -01		-502	30	40,0	M 30 x 2	34,5	70	50	37	25	

type		measurements [mm]					weight	rotational speed limit	basic load rating	
h	l	l ₁	l ₂	l ₃	SW	α [°]	n _{max} [rpm]	C [N]	C ₀ [N]	stat. rating [N]
BRTF 30	110	51	15,0	35	41	7,5	1,000	450	32500	24850

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952506913
Innendurchmesser	30 mm
Innendurchmesser	1.181" inch
Außendurchmesser	70 mm
Außendurchmesser	2.756" inch
Dicke	37 mm
Dicke	1.457" inch
Typ	SI
Gewicht	1000 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE