

Winkelgelenke SA

BRM10-00-502-DURBAL - BRM10-00-502-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brm10-00-502-durbal>

BRM10-00-502



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr VI

inner ring:
self-bearing steel, hardened, superfinished

lubrication:
aluminum-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DN 2425 D11A (sizes 6 to 10)
DN 21 412 H1 (sizes 12 to 30)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]									
Type	right-hand thread	M1-hand thread	d ₁	d ₂	d ₄	d ₅	l ₁	l ₂	l ₃	h	
BRM 10 -00	-502		10	M 10	12,0	28	14	10,5	48		
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating			
Type	l	l ₃	α [°]	[kg]	Y	v ₀	lim. C [N]	dyn. C ₁₀ [N]	stat. C ₀ [N]		
BRM 10	29	15	8,0	0,060	1,90	1,81	1225	4450	1450		

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952506975
Innendurchmesser	10 mm
Außendurchmesser	28 mm
Dicke	14 mm
Typ	SA
Gewicht	60 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE