

Winkelgelenke SA PM06-02-502-DURBAL - PM06-02-502-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/pm06-02-502-durbal>

PM06-02-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight		calculation factors		rotational speed limit		basic load rating		
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]	dyn.	stat.	C0	C0	
PM 06 -02	-502	6	M 10 x 1	8,5	24	14	14	14	10											
type		l1	l2	l3	h1	h2	u	z	alpha [°]											
PM 06	19	17	40,5	1,5	2,5	10,5	0,057			1,28	1,34	1300	2445	765						

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952507484
Innendurchmesser	6 mm
Innendurchmesser	0.236" inch
Außendurchmesser	24 mm
Außendurchmesser	0.945" inch
Dicke	14 mm
Dicke	0.551" inch
Typ	SA
Gewicht	57 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE