

# Winkelgelenke SA PM15-00-501-DURBAL - PM15-00-501-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/pm15-00-501-durbal>

## PM15-00-501



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]					measurements [mm]				weight	calculation factors	rotational speed limit	basic load rating	stat. rating
type	type/thread	d1	d2	d3	d4	d5	d7	b1	b2						
PM 15 -00	-501	15	M 20 x 1,5	18,5	42	26	20	14							
measurements [mm]															
type	l1	l2	l3	h1	h2	u	z	α [°]	α' [°]	weight [kg]	Y	Yc	nmax [min-1]	C [N]	C0 [N]
PM 15	62,5	30	100	3,0	2,5	6,5				0,310	2,07	2,17	975	5485	3270

## PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952507620
Innendurchmesser	15 mm
Außendurchmesser	42 mm
Dicke	20 mm
Typ	SA
Gewicht	310 g
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE