

Winkelgelenke SA PM17-00-502-DURBAL - PM17-00-502-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/pm17-00-502-durbal>

PM17-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USGA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]					weight		rotational speed limit		basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C [N]	C0 [N]	stat.	dyn.
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16									
measurements [mm]		weight		rotational speed limit		basic load rating											
type	l1	l2	l3	h1	h2	u	z	alpha [°]	alpha prime [°]	weight [kg]	Y	Yc	nmax [min-1]	C [N]	C0 [N]	stat.	dyn.
PM 17	62,5	36	105	3,5	2,5	7,0	0,401			2,35	2,46		875	5575	2680		

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952507675
Innendurchmesser	17 mm
Außendurchmesser	48 mm
Dicke	22 mm
Typ	SA
Gewicht	401 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE