

Gelenkköpfe SI

BRF16-60-501-DURBAL - BRF16-60-501-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/si/brf16-60-501-durbal>

BRF16-60-501



rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminum-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	light load thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	h	
BRF 16 -60	-501	16	22,0	M 16	19,0	42	27	21	15,0	64		
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.		
type	l	l ₁	l ₂	SW	α [°]	Y	l ₀	n _{max} [min ⁻¹]	C	C ₀	stat. C ₀ [N]	
BRF 16	28	8,0	22	22	8,0	0,224	2,24	2,35	975	4250	1600	

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952509280
Innendurchmesser	16 mm
Außendurchmesser	42 mm
Dicke	21 mm
Typ	SI
Gewicht	224 g
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1
Standard	Ohne Standard

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE