

Gelenklager GE

BRTM5-8-00-501-DURBAL - BRTM5-8-00-501-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/brtm5-8-00-501-durbal>

BRTM5/8-00-501



male thread:
long-term lubrication, low maintenance, shields, dimensions in inches

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [inches]								
type	right hand thread left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃
BRTM 5/8 -00	-501	.625	.6250-18 UNF	.748	1.653	.826	.590			
measurements [inches]		weight		rotational speed limit		basic load rating				
type	h	l	l ₂	α [°]	[kg]	rpm	C [N]	C ₀ [N]	C ₁₀ [N]	C ₅₀ [N]
BRTM 5/8	2.618	1.574	.944	7,0	0,182	975	13300	8900		

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3616060468314
Innendurchmesser	15.88 mm
Außendurchmesser	41.99 mm
Dicke	20.98 mm
Typ	GE
Gewicht	182 g
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1
Standard	Ohne Standard

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE