

Winkelgelenke SA

BRTM3-4-00-502-DURBAL - BRTM3-4-00-502-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brtm3-4-00-502-durbal>

BRTM3/4-00-502



male thread:
long-term lubrication, low maintenance, shields, dimensions in inches

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

roller ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [inches]									
type	right-hand thread	left-hand thread	d ₁	d ₂	class 2	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃
BRTM 3/4 -00		-502	.750	.7500-16 UNF		.956	1.968	.984	.708		
		measurements [inches]			weight	rotational speed limit	basic load rating				
type	h	l	b ₂	α	[kg]	rpm	C	C ₀			
BRTM 3/4	3.090	1.850	1.102	7,0	0,341	825	16655	11445			

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952509945
Innendurchmesser	19.05 mm
Innendurchmesser	3/4" inch
Außendurchmesser	49.99 mm
Außendurchmesser	1.968" inch
Dicke	24.99 mm
Dicke	0.984" inch
Typ	SA
Gewicht	341 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE