

Winkelgelenke SA

BRM1-4-00-502-DURBAL - BRM1-4-00-502-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brm1-4-00-502-durbal>

BRM1/4-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
dimensions in inches

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3425 D1/A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1/1)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [inches]								
type	right-hand thread / left-hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃
BRM 1/4 -00	-502	.250	.2500-28 UNF	.356	.787	.354	.265			
measurements [inches]		weight	calculation- factors	rotational speed limit	basic load rating					
type	h	l	α	Y	v _{max}	C	C ₀			
BRM 1/4	1.437	.866	.551	8,0	0,022	2,09	2,19	1350	2670	645

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952510255
Innendurchmesser	6.35 mm
Außendurchmesser	19.99 mm
Dicke	8.99 mm
Typ	SA
Gewicht	22 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE