

Winkelgelenke SA

BRM1-2-00-502-DURBAL - BRM1-2-00-502-DURBAL

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brm1-2-00-502-durbal>

BRM1/2-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
dimensions in inches

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3425 D1/A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1/1)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [inches]							
type	right-hand thread, left-hand thread	d ₁	d ₂ class 2	d ₃	d ₄	d ₅	b ₁	b ₂	b ₃
BRM1/2-00	-502	.500	5000-20 UNF	.574	1.311	.624	.472		
measurements [inches]		weight		calculation-factors		rotational speed limit		basic load rating	
type	h	l	l ₃	α [°]	Y	Y ₂	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
BRM1/2	2.460	1.496	.846	7,5	0,109	1,74	1,82	1125	4850 1850

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952510293
Innendurchmesser	12.7 mm
Außendurchmesser	33.3 mm
Dicke	15.85 mm
Typ	SA
Gewicht	109 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE