


Nadelhülsenlager FC-20-NADELLA - FC-20-NADELLA

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/fc-20-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F ₂ mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min*	Suitable needle bush
20	FC-20	20	26	16	32.6	11000	HK2012

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Mounting		Max. mm	Min. mm	
20	25.976	19.970	20.007	38	Max. mm	Min. mm	Max. mm	Min. mm	0.021

PRODUKTMERKMALE

Marke	NADELLA
N° Ean13	3663952529455
Innendurchmesser	20 mm
Innendurchmesser	0.787" inch
Außendurchmesser	26 mm
Außendurchmesser	1.024" inch
Dicke	16 mm
Dicke	0.63" inch
Gewicht	21 g
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE