


# Nadelhülsenlager FCS-35-NADELLA - FCS-35-NADELLA

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/fcs-35-nadella>

## Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F <sub>0</sub> mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min	Suitable needle bush
35	FCS-35	35	42	20	107.0	6100	HK3512

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Max. mm	Min. mm	Max. mm	Min. mm	
35	41.972	34.964	35.009	56	35.000	34.989	41.988	41.972	0.048

## PRODUKTMERKMALE

Marke	NADELLA
N° Ean13	3663952529509
Innendurchmesser	35 mm
Außendurchmesser	42 mm
Dicke	20 mm
Gewicht	48 g
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE