

Rillenkugellager einreihig NG040-CP0-RBC - NG040-CP0-RBC

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/ng040-cp0-rbc>

**RADIAL CONTACT, C-TYPE
THIN SECTION BALL BEARINGS**

- S2100 Steel with Thin Dense Chrome Coating
- Large Diameter
- Light Weight
- Small Cross Section
- Snap-Over Ball Separator

Series: **NG**
Cross-Section Size: **1"**

| N | |
|-------------------------------|--|
| Material Type | Single S2100 - TSC |
| Balls | 440C |
| Typical Hardness | HRC 70 - 72 |
| Corrosion Resistance Material | Stainless |
| Friction Resistance | Good |
| Sealing Resistance | Very Good |
| Preservative | May be supplied with or without preservative |

| PART NUMBER | B Bore | D Outside Diameter | W Width | NOMINAL DIMENSIONS | | | | Ball Diameter |
|--------------|---------|--------------------|---------|---------------------------|---------------------------|-------------------------------|---------------|---------------|
| | | | | L _i Inner Ring | L _o Outer Ring | r _s Housing Fillet | Ball Diameter | |
| NG040CP0-RBC | 101.595 | 152.408 | 25.400 | 4.762 | 5.207 | 0.260 | 12 | |

| Ball Quantity | Approx. Weight | LOAD RATINGS | | | | | | Limiting Speed (RPM) | | | | |
|---------------|----------------|--------------|---------|--------|---------|--------|---------|----------------------|-------|--------|-------|-------|
| | | Radial | | Thrust | | Moment | | | | | | |
| | | Static | Dynamic | Static | Dynamic | Static | Dynamic | | | | | |
| 12 | 1.633 | 8,273 | 35,220 | 6,706 | 28,833 | 12,988 | 27,600 | 16,442 | 1,482 | 16,442 | 2,200 | 4,850 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | RBC |
| N° Ean13 | 3663952538907 |
| Innendurchmesser | 101.595 mm |
| Innendurchmesser | 4" inch |
| Außendurchmesser | 152.408 mm |
| Außendurchmesser | 6" inch |
| Dicke | 25.4 mm |
| Dicke | 1" inch |
| Gewicht | 1633 g |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE