



# Rillenkugellager einreihig NAA15-AG0-RBC - NAA15-AG0-RBC


<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/naa15-ag0-rbc>

**ANGULAR CONTACT, A-TYPE**  
**THIN SECTION BALL BEARINGS**





- S2100 Steel with Thin Dense Chrome Coating
- Large Diameter
- Light Weight
- Small Cross Section
- Circular Pocket Ball Separator



Series: **NAA**  
Cross Section Size: **3/16"**

Mechanical Type		N
Ring	S2100 - TSC	
Balls	440C	
Typical Hardness	HRC 70 - 72	
Wear Resistance Material	Sand	
Friction Resistance	Sand	
Sealing Resistance	Very Good	
Preservation	May be supplied with or without preservation	

PART NUMBER*	B Bore	D Outside Diameter	W Width	NOMINAL DIMENSIONS					Ti	Ball Diameter				
				U - Inner Ring	U <sub>2</sub> - Outer Ring	U <sub>3</sub> - Counter bore	U <sub>4</sub> - Groove	U <sub>5</sub> - Groove						
NAA15AG0RBC	1.5200	38.100	4.7630	0.1875	4.763	1.841	41.68	1.734	44.04	1.735	41.00	0.015	0.38	300

Ball Quantity	Approx. Weight	LOAD RATINGS						Limiting Speed (RPM)						
		Radial		Thrust		Moment								
		Static	Dynamic	Static	Dynamic	Static	Dynamic							
43	0.24	0.018	480	2,140	300	1,200	1,200	0,140	1,150	4,500	900	900	900	11,000

## PRODUKTMERKMALE

Marke	RBC
N° Ean13	3663952540085
Innendurchmesser	38.1 mm
Außendurchmesser	47.63 mm
Dicke	4.763 mm
Gewicht	18 g
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE