Rillenkugellager einreihig
3004-NS-NICE - 3004-NS-NICE

https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/3004-ns-nice



3000 Series® Semi-Ground Radial Bearings — NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1500 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

TO CLEAR r; B; d; D

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +.005 +0.13 -.000 -.00	O.D. D (in) (mm) +.0000 +.00 -.0005 [4] -0.013
3004™					NS	0.3750 9.525	0.8750 22.225

	BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm) +.005 +.00 -.005 -.13	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W [3] (lbs) (kg)	d_a min (in) (mm)	D_a max (in) (mm)	r max (in) (mm)
0.2813 [2] 7.1450	325 1446	255 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.015 0.38

[2] Width for sealed versions = 0.3438 (8.733)
[3] Weights given are for greased and sealed versions
[4] 3038 and larger +.0000/-.0006 (+.000/-.015)

123BEARING

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558103
Innendurchmesser	9.525 mm
Außendurchmesser	22.225 mm
Dicke	7.145 mm
Gewicht	10 g
Verpackung	1

kontakt@123kugellager.de
0800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE