


# Rillenkugellager einreihig 3004-DS-NICE - 3004-DS-NICE






<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/3004-ds-nice>

**3000 Series® Semi-Ground Radial Bearings**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

**NICE™**



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING						BORE <b>d</b> (in) (mm)	O.D. <b>D</b> (in) (mm)
	+0.005 -0.13 -0.005	+0.005 -0.13 -0.005	+0.005 -0.13 -0.005	+0.005 -0.13 -0.005	+0.005 -0.13 -0.005	+0.005 -0.13 -0.005	+0.005 -0.13 -0.005
3004™			DS			9.525	22.225

BASIC LOAD RATINGS		WEIGHT		ABUTMENT AND FILLET DIMENSIONS		
WIDTH <b>B</b> (in) (mm)	DYNAMIC <b>C</b> (lbs) (N)	STATIC <b>Co</b> (lbs) (N)	<b>W</b> (lbs) (kg)	<b>d<sub>a</sub> min</b> (in) (mm)	<b>D<sub>a</sub> max</b> (in) (mm)	<b>r max</b> (in) (mm)
0.2813 7.1450	325 1448	255 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.015 0.38

① Width for sealed versions = 0.3438 (8.733)
② Weights given are for greased and sealed versions  
③ 3038 and larger +.0005/-0.005 (-.000/-0.15)

## PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558127
Innendurchmesser	9.525 mm
Außendurchmesser	22.225 mm
Dicke	7.145 mm
Gewicht	10 g
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE