


Rillenkugellager einreihig 3005-SC-NICE - 3005-SC-NICE

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/3005-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- W/LOW RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|---------|-------------|-------------|---------------|---------------|----------------------|------------------------------------|-------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3005™ | | SC | | | | +0.005 +0.13 -0.000 -0.00 | +0.000 +0.00 -0.013 -0.013 |
| | | | | | | 0.3125 7.938 | 0.9063 23.020 |

| BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|------------------------------|-------------------------|------------------------------------|------------------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lbs) (N) | W ⓪ (lbs) (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) |
| 0.3125 7.938 | 350 1558 | 300 1335 | 0.04 0.02 | 0.503 12.78 | 0.778 19.76 |
| | | | | | 0.012 0.30 |

⓪ Weights given are for greased and sealed versions
⓪ 3038 and larger +0.000/-0.006 (-0.000/-0.15)

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | NICE |
| N° Ean13 | 3663952558165 |
| Innendurchmesser | 7.938 mm |
| Außendurchmesser | 23.02 mm |
| Dicke | 7.938 mm |
| Gewicht | 20 g |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE