

Rillenkugellager einreihig 3035-SC-NICE - 3035-SC-NICE

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/3035-sc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3035™		SC				+0.005 -0.13 -0.00	+0.000 -0.50 -0.0005
						2.7500 19.050	1.7500 44.450

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5795	1025 4561	0.20 0.09	0.965 24.51	1.530 38.85	0.025 0.64

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3035 and larger +0.0005/-0.005 (-0.001/-0.13)

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558769
Innendurchmesser	19.05 mm
Innendurchmesser	3/4" inch
Außendurchmesser	44.45 mm
Außendurchmesser	1 3/4" inch
Dicke	12.7 mm
Dicke	1/2" inch
Gewicht	90 g
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE