

Rillenkugellager einreihig 3040-SC-NICE - 3040-SC-NICE

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/3040-sc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|---------|-------------|-------------|---------------|---------------|------|-------------------------------------|-------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3040™ | | SC | | | | +0.005 +0.13 -0.000 -0.005 | +0.000 +0.00 -0.013 -0.005 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|-----------------------------|-----------------------------|--------------------------------|--------------------------------|------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC Co (lb) (N) | W ^⓪ (lb) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.5625 14.288 | 1480 6598 | 1350 6008 | 0.29 0.13 | 1.113 28.27 | 1.760 44.70 | 0.035 0.89 |

^⓪ Weights given are for greased and sealed versions
^⓪ 3038 and larger +0.0005/-0.005 (+0.001/-0.125)

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | NICE |
| N° Ean13 | 3663952558868 |
| Innendurchmesser | 22.225 mm |
| Außendurchmesser | 50.8 mm |
| Dicke | 14.288 mm |
| Gewicht | 130 g |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE