


Rillenkugellager einreihig 7520-DL-NICE - 7520-DL-NICE

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/7520-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES, RELATED TO THE ISO 5201 CLASSIFICATION
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- WIDE SPEED RANGE - 5000 - 10000 RPM
- THROUGH HARDENED BEARING STEEL
- RETURNING DESIGN
- WIDEN RETURNING STANDARD
- DOUBLE ROLLER STANDARD
- USING LUBRICATING OILS - 10 CONTACT BALLS WITH TIGHT SEALS - 10 CONTACT BALLS WITH TIGHT SEALS - 10 CONTACT BALLS WITH TIGHT SEALS
- AVAILABLE IN SINGLE OR DOUBLE ROLLER STANDARD
- ALL BEARINGS MUST BE OILED AND OILS MUST BE CHANGED TO 100% OIL
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHOCK & HIGH TEMPERATURES ARE A FACTOR



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7520™	1.2500 31.75	2.6250 65.09	0.7500 19.05	0.0625 1.59	0.8750 22.23	1.672 42.47

PRINCIPLE DIMENSIONS				BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
G (in) (mm)	H (in) (mm)	J (in) (mm)	R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.190 4.83	0.065 1.65	2.7856 70.25	0.035 0.89	5360 23852	2620 11659	0.57 0.26	1.500 38.10	2.312 58.72	0.036 0.89

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLQ)
② Tolerance for 7514™ and larger is +.0000/-0.0006 (+.0001/-0.016)
③ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of RBC Nippon Bearings

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473332
Innendurchmesser	31.75 mm
Außendurchmesser	65.09 mm
Dicke	19.05 mm
Gewicht	260 g
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE