

Rillenkugellager einreihig 616-V-NICE - 616-V-NICE

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/616-v-nice>

600 Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- TOP STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS LOOSE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE

BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)		
616™	V	+0.010-0.000 +0.25-0.00	+0.010 +0.25	+0.010 +0.25	+0.010 +0.25	23	1/4 6.35
		1.25 31.75	1.275 32.38	2.1102 53.53	0.25 6.35		0.4 0.18

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10	50	100	250	500	1000
(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
(N)	(N)	(N)	(N)	(N)	(N)
1794	1449	1069	579	419	298
7983	6448	4757	2577	1865	1328

Notes
Balls - Carbon Steel Grade 52100
Washers - Carbon Steel Case Hard
Bands - Carbon Steel Soft
Bearings Oiled with a Rust Preventative
All Bearings Marked on Band with "Designation Nice USA" as Shown

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952560496
Innendurchmesser	31.75 mm
Außendurchmesser	59.53 mm
Dicke	15.88 mm
Gewicht	180 g
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE