

# Zubehör

## 7615-DL-NICE - 7615-DL-NICE

<https://www.123kugellager.de/kugellager-gehauselager/gehauselager/zubehor/7615-dl-nice>

**7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't)** **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE: 5000 - 8000 RPM
- PRECISION MANUFACTURE
- SHOCK RESISTANT
- WIPER CASE STANDARD
- STANDARD SEALER STANDARD
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHIP END DESIGN, WITH POLE POSITIONED AS AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EXACTLY SPECIFIED DIMENSIONS AND SUPERIOR QUALITY ARE REQUIRED

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
7615™ Ø	+0.0008 +0.000 -0.0000 -0.000	+0.0000 +0.000 -0.0005 Ø -0.013	+0.000 0.000	0.000 0.000	1.308 33.17	+0.005 +0.13 -0.005 -0.13

PRINCIPLE DIMENSIONS					BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Dynamic C (lb) (N)	Static C <sub>0</sub> (lb) (N)	W (kg)
0.042 1.07	2.158 54.77	1.179 29.95	0.492 12.50	0.261 6.63	1/4-28 6.35	0.035 0.89	2970 13217	1560 6998

When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)  
 Tolerance for 7615™ and larger is +0.0000/-0.0005 (+0.000/-0.015)  
 Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

## PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473462
Innendurchmesser	23.81 mm
Außendurchmesser	33.17 mm
Dicke	15.88 mm
Gewicht	180 g
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE