

Zubehör N6916-NICE - N6916-NICE

<https://www.123kugellager.de/kugellager-gehauselager/gehauselager/zubehor/n6916-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

EASY TO USE DIMENSIONS

- MEDIUM LOADS
- MAX SPEED RANGE: 2000 - 3000 RPM
- THROUGH HARDENED
- RETAINED DESIGN
- NYLON RETAINER STANDARD
- DOUBLE SEALER STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm) Bolt Centers	H (in) (mm)
	SUFFIX	+0.005	+0.000	+0.000	+0.000				
		+0.13	+0.00	+0.00	+0.00				
		-0.000	-0.005	-0.000	-0.000				
		-0.00	-0.15	-0.15	-0.15				
N6916™	B	1.000	2.000	0.583	1.063	1.293	0.500	3.250	4.125
		25.40	50.80	14.29	26.99	32.84	12.70	82.55	104.78

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT	
J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	O 2-Set Screws	P (in) (mm) Hole Dia.	S (in) (mm)	C (lbs) (N)	C ₀ (lbs) (N)	W (lbs) (kg)
2.250	0.438	0.688	1.125	0.062	10-32	0.4375	0.062	1870	1350	0.33
57.15	11.11	17.48	28.58	1.57		11.11	1.57	8322	6008	0.15

When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B, for example 6904™B. Housings no longer carry part numbers.
Tolerance for 6912 and larger is +.0000/-0.0006 (+000/-016) Weights given are for greased and sealed version with flange mount.

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952564814
Innendurchmesser	25.4 mm
Innendurchmesser	1" inch
Außendurchmesser	50.8 mm
Außendurchmesser	2" inch
Dicke	14.29 mm
Dicke	9/16" inch
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE