


Gelenkköpfe TSM

MX-05-4-DUNLOP - MX-05-4-DUNLOP

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/tsm/mx-05-4-dunlop>

MALE ROD ENDS **DUNLOP**



MALE ROD ENDS

Description:
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 40, heat treated to 85/90 tons/m² tensile, Phosphated all over.
Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M40, Heat Treated to 85/90 tons/m² tensile and Phosphate all over.

Balls: Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
MX-05-R	MX-05-L	20.624	3.95	3.20	3.75	3.12	1.625	1.662	3/16 UNF	22	11770

Interchange table

Dunlop	Rose	NMB
MX-M (Metric)	RJ-M	RJ-M
MX (Imperial)	RJ-I	RJ-I

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.
'G' in part number denotes grease nipple is fitted.

PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060550644
Innendurchmesser	6.35 mm
Außendurchmesser	20.624 mm
Dicke	9.525 mm
Typ	TSM
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1
Standard	Ohne Standard

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE