


# Gelenkköpfe TSM

## MXL-05-4-DUNLOP - MXL-05-4-DUNLOP

<https://www.123kugellager.de/kugellager-gehauselager/gelenkkopfe-gelenklager/tsm/mxl-05-4-dunlop>

**MALE ROD ENDS** **DUNLOP**



**MALE ROD ENDS**

**MX SERIES**

**Description:**  
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

**Material Specifications:**  
Housing: B17M 40, heat treated to 85/90 tons/m<sup>2</sup> tensile, Phosphated all over.  
Ball: 100Cr 6, heat treated, Phosphated all over.

**Features:**  
Metric and Imperial sizes available  
Can be used in application involving shock loading and high frequency oscillation.

**Possible Applications:**  
Medium / heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment and motor sport.

**Temperature Range:**  
-40°C to +150°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Forged B17M40, Heat Treated to 85/90 tons/m<sup>2</sup> tensile and Phosphated all over. **Balls:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
MXL-05-4		20.624	3.95	3.20	3.75	3.12	1.625	1.062	3/16 UNF	22	11770

**Interchange table**

Dunlop	Rose	NMB
MXL-Metric	RRL-M	RRL-M
MX-Imperial	RRL-I	RRL-I

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.  
'0' in part number denotes grease nipple is fitted.

## PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060550859
Innendurchmesser	6.35 mm
Außendurchmesser	20.624 mm
Dicke	9.525 mm
Typ	TSM
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1
Standard	Ohne Standard

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE