

## Nadelhülsenlager TAM3220-IKO - TAM3220-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/tam3220-iko>



Boundary dimensions			Standard mounting dimensions mm						Basic dynamic load rating		Basic static load rating		Allowable rotational speed (1)	Assembled inner ring
mm			Shaft dia.		Housing bore dia.				C	CW	N		rpm	
Fr	D	C	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	N	N	rpm	
32	42	20	3.4		32	32	32	32	25400	38600	11000	RT 280		

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3616060599513
Innendurchmesser	32 mm
Innendurchmesser	1.26" inch
Außendurchmesser	42 mm
Außendurchmesser	1.654" inch
Dicke	20 mm
Dicke	0.787" inch
Grenzdrehzahl	11000 rpm
Dynamische Belastung	25.4 kN
Statische Belastung	38.6 kN
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE