

Geschlitzte wellfederscheibe

SWSW-190.50-169.93-0.81-6-SS - SWSW-190.50-169.93-0.81-6-SS

<https://www.123kugellager.de/zubehor/unterlegscheibe/geschlitzte-wellfederscheibe/sws-190.50-169.93-0.81-6-ss>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (+/-15 % Newton)
DB = Bearing's outside diameter
Dr = Free fit in hole diameter
N = Number of waves



Split Wave Spring Washers

Part Number	Di (mm)	t (mm)	L1 (N)	H1 (mm)	Do (mm)	N	H (mm)
WWG0750038010S	169,93	0,81	489,304	3,962	190,50	6	9,14

PRODUKTMERKMALE

Marke	GEN
Innendurchmesser	169.93 mm
Dicke	0.81 mm
Material	INOX
Verpackung	1
Last an L1	489.304 N
Belastung in der Höhe	3.962
Außendurchmesser (max.)	190.5 mm
Anzahl der Wellen	6

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE