

## Wellenfedern (rundraht) WSRW-31.75-3-1.65 - RW-0125

<https://www.123kugellager.de/zubehor/unterlegscheibe/wellenfedern-rundraht/rw-0125>

Do = Outside diameter (max) (mm)  
Di = Inside diameter (min) (mm)  
t = Thickness (mm)  
H = Free height approx.  
H1 = Load at height  
L1 = Load at L1 (+/-15 % Newton)  
DB = Bearing's outside diameter  
Dh = Free fit in hole diameter  
Dr = Free fit over hole diameter  
N/Wx = Number of waves  
Pf = Load at flat (approx.)  
d = Wire diameter



Wave Springs - Round Wire

Part Number	Wx	Lo (mm)	L1 (mm)	Dr (mm)	Dh (mm)	d (mm)	P1 (N)
RW-0125	3	3,51	2,79	27,46	31,75	1,65	490

### PRODUKTMERKMALE

Marke	GEN
Anzahl der Wellen	3
Freie Höhe	3.51 mm
Verpackung	1
Höhe bei Belastung	2.79
Spiel auf dem Durchmesser der Achse	27.46 mm
Opera in einer Wohnung mit einem Durchmesser von	31.75 mm
Durchmesser des Fadens	1.65 mm

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE