

# Kegelrollenlager 32956-JR-JTEKT - 32956-JR-JTEKT

<https://www.123kugellager.de/kugellager-gehauselager/zylinderrollenlager/kegelrollenlager/32956-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)             |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                    |                |                    |       |
|--------------------------------------|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|--------------------|-------|
| d                                    | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                    |                |                    |       |
| 280                                  | 380                | 63.5                     | 63.5                 | 48                      | 3                    | 2.5                  | 780                  | 1630                                 | 770                  | 1000                      | 32956JR            |                |                    |       |
| Dimension series to ISO 355 (Refer.) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors |                | (Refer.) Mass (kg) |       |
|                                      |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min.    | D <sub>1a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min.                 | r <sub>1a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                    |       |
| 4EC                                  | 75.1               | 294                      | 298                  | 368                     | 347                  | 368                  | 11                   | 15.5                                 | 2.5                  | 2                         | 0.43               | 1.39           | 0.76               | 20.14 |

## PRODUKTMERKMALE

|                  |               |
|------------------|---------------|
| Marke            | JTEKT         |
| N° Ean13         | 4549250125812 |
| Innendurchmesser | 280 mm        |
| Innendurchmesser | 11.024" inch  |
| Außendurchmesser | 380 mm        |
| Außendurchmesser | 14.961" inch  |
| Dicke            | 63.5 mm       |
| Dicke            | 2 1/2" inch   |
| Verpackung       | 1             |

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE