

Kegelrollenlager 685-672-JTEKT - 685-672-JTEKT

<https://www.123kugellager.de/kugellager-gehauselager/zylinderrollenlager/kegelrollenlager/685-672-jtekt>

Single-row tapered roller bearings
inch series

Koyo

The image displays two technical cross-sectional views of a single-row tapered roller bearing. The left view shows the bearing with dimensions labeled: d (inner diameter), D (outer diameter), T (thickness), B (width), C (height), r_{max} (maximum fillet radius), r_{min} (minimum fillet radius), $\phi D_s \phi d_s$ (inner hole diameter), and $\phi d_s \phi D_s$ (outer hole diameter). The right view shows the bearing with dimensions labeled: C (height), r (fillet radius), D (outer diameter), B (width), ϕd (inner diameter), and α (taper angle).

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_{max}	r_{min}	C_0	C_{10}	Grease lub.	Oil lub.
98.425	168.275	41.275	41.275	30.162	3.6	3.2	224	349	2 200	3 000

Mounting dimensions (mm)		Constant		Axial load factors		(Refer.) Mass (kg)							
Inner ring	Outer ring	e	e	Y_1	Y_2	Inner ring	Outer ring						
685	672	38.6	116.0	109.0	149.0	160.0	3.6	3.2	0.47	1.28	0.70	2.29	1.22

PRODUKTMERKMALE

Marke	JTEKT
N° Ean13	3663952429878
Innendurchmesser	98.425 mm
Außendurchmesser	168.275 mm
Dicke	41.275 mm
Verpackung	1

kontakt@123kugellager.de
0800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE