

Zylinderrollenlager NNU4944K-JTEKT - NNU4944K-JTEKT

<https://www.123kugellager.de/kugellager-gehauselager/zyylinderrollenlager/zyylinder/nnu4944k-jtekt>

Double-row cylindrical roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds (min ⁻¹) | | Bearing No. | |
|--------------------------|-----|----|------------------|-------------------------|----------------|-----|--------------------------------------|-------------|-------------|--|
| d | D | B | r _{min} | F _w | E _a | C | C ₁₀₇ | Grease lub. | Oil lub. | NN Cylindrical bore Tapered bore |
| 220 | 300 | 80 | 2.1 | 244 | — | 501 | 1 220 | 1 700 | 2 000 | |

| | Mounting dimensions (mm) | | Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | |
|----------|--------------------------|---------------------|--------------------------|---------------------|---------------------|---------------------|--------------------|--------------|
| | d _a min. | d _a max. | d _a min. | d _a max. | D _a min. | r _s max. | Cylindrical bore | Tapered bore |
| NNU4944K | 231 | 241 | 248 | 289 | — | 2 | 16.7 | 16.0 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | JTEKT |
| N° Ean13 | 3663952473444 |
| Innendurchmesser | 220 mm |
| Außendurchmesser | 300 mm |
| Dicke | 80 mm |
| Gewicht | 16000 g |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE