

Rillenkugellager einreihig W626-ZZ-JTEKT - W626-ZZ-JTEKT

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/w626-zz-jtekt>

Boundary dimensions

Open type Shielded Shielded Locating snap ring

ZZ / 2RS / 2RD NR

(mm) / (in) / (mm) / (in) / (mm) / (in) / (mm) / (in) / (mm) / (in) / (mm) / (in) / (mm) / (in) / (mm) / (in)

(M) Extra-small dimensions: 2500 / 6900 / 16000 / 6000 / 6200 / 6300 / 6400

Extra small Standard shielded ZZ

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)			Fatigue load factor	Limiting speeds (min-1)
	d	D	B	r (min)	C _r	C _{0r}	C _u		
626 ZZ	6	19	6	0.3	2.9	0.89	0.04	12.3	Grease lub. 35000

PRODUKTMERKMALE

Marke	JTEKT
N° Ean13	3616060623225
Innendurchmesser	6 mm
Wasserdichtheit	Deckscheiben auf beiden Seiten
Außendurchmesser	19 mm
Dicke	6 mm
Grenzdrehzahl	35000 rpm
Dynamische Belastung	2.9 kN
Statische Belastung	0.89 kN
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE