


# Kegelrollenlager 2560X-2526X-TIMKEN - 2560X-2526X-TIMKEN

<https://www.123kugellager.de/kugellager-gehauselager/zylinderrollenlager/kegelrollenlager/2560x-2526x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |        |         | Load Ratings                          |                         |  |                         |                       |       | Part Number |       |
|--------------------|--------|---------|---------------------------------------|-------------------------|--|-------------------------|-----------------------|-------|-------------|-------|
| Bore d             | O.D. D | Width B | Dynamic <sup>(1)</sup> C <sub>1</sub> | Factor <sup>(2)</sup> e | Dynamic <sup>(1)</sup> C <sub>02</sub> | Factor <sup>(2)</sup> K | Static C <sub>0</sub> | Inner | Outer       |       |
| mm                 | mm     | mm      | N                                     |                         | N                                      |                         | N                     |       |             |       |
| 38 090             | 72 090 | 23 812  | 82700                                 | 0.27                    | 21700                                  | 10200                   | 2.14                  | 84400 | 2560X       | 2526X |
| 1.1811             | 2.8348 | 0.9375  | 18500                                 |                         | 4880                                   | 2208                    |                       | 21280 |             |       |

| Bearing Dimensions |         |                          |   |   |   |   |                                    |                               |                | Geometry Factors |                |     | Bearing Weight |      |
|--------------------|---------|--------------------------|---|---|---|---|------------------------------------|-------------------------------|----------------|------------------|----------------|-----|----------------|------|
| Width B            | Width C | ER. Dr. α <sup>(1)</sup> | Max Shaft Fillet Radius R <sub>1</sub> <sup>(2)</sup> | Backing Shoulder Dia. d <sub>s</sub> <sup>(2)</sup> | Max Housing Fillet Radius r <sub>1</sub> <sup>(2)</sup> | Backing Shoulder Dia. D <sub>s</sub> <sup>(2)</sup> | Cage A <sub>1</sub> <sup>(1)</sup> | A <sub>2</sub> <sup>(1)</sup> | G <sub>1</sub> | G <sub>2</sub>   | C <sub>3</sub> |     |                |      |
| mm                 | mm      | mm                       | mm  | mm  | mm  | mm  | mm                                 | mm                            |                |                  |                | kg  |                |      |
| 25.207             | 19.050  | -8.8                     | 2.8   | 38.0  | 33.5  | 2.8   | 65.0                               | 61.8                          | 8.8            | 8.8              | 23.6           | 9.8 | 0.0608         | 6.90 |
| 0.9983             | 0.7500  | -0.34                    | 0.08  | 1.42  | 1.56  | 0.08  | 2.56                               | 2.40                          | 0.03           | 0.04             |                |     |                | 1.11 |

## PRODUKTMERKMALE

|            |               |
|------------|---------------|
| Marke      | TIMKEN        |
| N° Ean13   | 3663952136462 |
| Verpackung | 1             |

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE