


Nadelhülsenlager BAM108-IKO - BAM108-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam108-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
15.875 (5/8)	—	—	—	—	—	—	BAM 108	9.9	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _w	D	C	h ₂ Shaft dia. h8 Max.	H7 Housing bore dia. Min.	J7 Max.	J7 Min.	N	N	rpm	IRB 68-1
15.875 (5/8)	20.638 (3/4)	12.70 (500)	1.3 (15.875)	15.864	20.650	20.629	5 420	7 310	25 000	IRB 68-1

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952172958
Innendurchmesser	15.88 mm
Innendurchmesser	5/8" inch
Außendurchmesser	20.64 mm
Außendurchmesser	13/16" inch
Dicke	12.7 mm
Dicke	1/2" inch
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE